

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : DRY FLEX® 1 2-IN-1 - Component A

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use
Use of the substance/mixture : Elastic repair compound
Product only to be used in combination with component B.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Repair Care International B.V.
Cartografenweg 34
NL- 5141 MT Waalwijk
Nederland
T + 31(0) 416 650095
info@repair-care.com - www.repair-care.com

1.4. Emergency telephone number

Country/Area	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA Belfast	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to GB CLP (SI 2019:720 as amended)

Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment – Chronic Hazard, Category 2 H411
Full text of H- and EUH-statements: see section 16


Adverse physicochemical, human health and environmental effects

Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to GB CLP (SI 2019:720 as amended)

Hazard pictograms (GB CLP) :



Signal word (GB CLP) : Warning

Contains : oxirane, mono[(C12-14-alkyloxy)methyl] derivs.; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol; ISOPROPYLIDENEDIPHENOL DIGLYCIDYL ETHER

Hazard statements (GB CLP) : H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (GB CLP) : P261 - Avoid breathing vapours, mist.
P264 - Wash hands thoroughly after handling.
P280 - Wear protective gloves, protective clothing, eye protection.
P333+P313 - If skin irritation or rash occurs: Get medical advice.
P391 - Collect spillage.
P501 - Dispose of contents and container to an approved waste disposal plant.

EUH-statements (GB CLP) : EUH205 - Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards

No additional information available

DRY FLEX® 1 2-in-1 - Component A

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to GB CLP (SI 2019:720 as amended)
bis-[4-(2,3-epoxipropoxy)phenyl]propane	CAS-No.: 1675-54-3 EC-No.: 216-823-5 UK Index-No.: 603-073-00-2	30 – 50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	CAS-No.: 9003-36-5 EC-No.: 500-006-8	15 – 20	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	CAS-No.: 68609-97-2 EC-No.: 271-846-8 UK Index-No.: 603-103-00-4	15 – 20	Skin Irrit. 2, H315 Skin Sens. 1, H317

Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
bis-[4-(2,3-epoxipropoxy)phenyl]propane	CAS-No.: 1675-54-3 EC-No.: 216-823-5 UK Index-No.: 603-073-00-2	(5 ≤ C ≤ 100) Eye Irrit. 2; H319 (5 ≤ C ≤ 100) Skin Irrit. 2; H315

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Take off contaminated clothing. Wash skin with soap and water. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting without medical advice. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Presents no particular fire or explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon oxides (CO, CO ₂).

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

DRY FLEX® 1 2-in-1 - Component A

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Scoop absorbed substance into closing containers. Store away from other materials.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Provide good ventilation in process area to prevent formation of vapour. Avoid all eye and skin contact and do not breathe vapour and mist.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Always wash hands after handling the product. Take off contaminated clothing and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well-ventilated place.
Incompatible products : Oxidizing agents. Strong acids. Alkalines.
Storage temperature : 10 – 30 °C
Heat and ignition sources : Keep away from heat and direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment:

Protective clothing. Gloves. Protective goggles.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses. DIN EN 166

DRY FLEX® 1 2-in-1 - Component A

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

8.2.2.2. Skin protection

Skin and body protection:

Long sleeved protective clothing. ISO 13688

Hand protection:

Wear suitable gloves resistant to chemical penetration. Chemical resistant gloves (according to European standard NF ISO 374-1 or equivalent)

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Gloves	Nitrile rubber (NBR), Butyl rubber, Polyvinylchloride (PVC)	6 (> 480 minutes)	>0.11		ISO 374-1

8.2.2.3. Respiratory protection

Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Paste.
Colour	: red.
Odour	: characteristic.
Odour threshold	: Not available
pH	: Not available
Melting point	: < 0 °C
Freezing point	: Not available
Boiling point	: > 100 °C
Flash point	: > 100 °C
Explosive limits	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Relative vapour density at 20°C	: > 1 (Air = 1)
Relative density	: 1,16 (Water = 1)
Density	: Not available
Solubility	: Poorly soluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
Viscosity, kinematic	: Not available
Explosive properties	: Not available

9.2. Other information

VOC content	: Without VOC (volatile organic compounds)
Particle characteristics	: Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

DRY FLEX® 1 2-in-1 - Component A

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid extremely high (> 50 ° C) or low (<5 ° C) temperatures.

10.5. Incompatible materials

Oxidizing agents. Strong acids. Alkalines.

10.6. Hazardous decomposition products

Combustion generates: Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

LD50 oral rat	≈ 26800 mg/kg
---------------	---------------

LD50 dermal rabbit	> 4000 mg/kg
--------------------	--------------

bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)

LD50 oral rat	> 2000 mg/kg
---------------	--------------

LD50 dermal rat	> 2000 mg/kg
-----------------	--------------

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)

Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

STOT-single exposure : Not classified (Based on available data, the classification criteria are not met)

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

LC50 - Fish [1]	> 100 mg/l (OECD 203; Oncorhynchus mykiss)
-----------------	--

EC50 72h - Algae [1]	843,75 mg/l (OECD 201; Pseudokirchneriella subcapitata)
----------------------	---

NOEC chronic crustacea	56 mg/l (OECD 211; Daphnia magna)
------------------------	-----------------------------------

NOEC chronic algae	500 mg/l (OECD 201; Pseudokirchneriella subcapitata)
--------------------	--

bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)

LC50 - Fish [1]	1,2 mg/l (Oncorhynchus mykiss)
-----------------	--------------------------------

EC50 - Crustacea [1]	2,7 mg/l (Daphnia magna)
----------------------	--------------------------

ErC50 algae	> 11 mg/l (Scenedesmus capricornutum)
-------------	---------------------------------------

NOEC chronic crustacea	0,3 mg/l (Daphnia magna)
------------------------	--------------------------

NOEC chronic algae	4,2 mg/l (Scenedesmus capricornutum)
--------------------	--------------------------------------

DRY FLEX® 1 2-in-1 - Component A

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

12.2. Persistence and degradability

DRY FLEX® 1 2-IN-1 - Component A

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)

Persistence and degradability	Biodegradability in water: no data available.
-------------------------------	---

bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

12.3. Bioaccumulative potential

oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

Partition coefficient n-octanol/water (Log Pow)	3,77 (20 °C)
---	--------------

bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)

Partition coefficient n-octanol/water (Log Pow)	3,242 (25 °C; pH 7,1)
---	-----------------------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.
Ecological waste information	: Avoid release to the environment.
European List of Waste (LoW, EC 2000/532)	: 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances
HP Code	: HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP13 - "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
Special provision(s) applied : 375	Special provision(s) applied : 969	Special provision(s) applied : A197	Special provision(s) applied : 375
These substances when carried in single or combination packagings containing a net quantity per single or inner packaging of 5 l or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of the transport regulations provided the packagings meet the general provisions.			
14.1. UN number			
UN 3082	UN 3082	UN 3082	UN 3082

DRY FLEX® 1 2-in-1 - Component A

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

ADR	IMDG	IATA	RID
14.2. UN proper shipping name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) CONTAINS : bis-[4-(2,3-epoxipropoxi)phenyl]propane)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) CONTAINS : bis-[4-(2,3-epoxipropoxi)phenyl]propane)	Environmentally hazardous substance, liquid, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) CONTAINS : bis-[4-(2,3-epoxipropoxi)phenyl]propane)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) CONTAINS : bis-[4-(2,3-epoxipropoxi)phenyl]propane)
Transport document description			
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) CONTAINS : bis-[4-(2,3-epoxipropoxi)phenyl]propane), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) CONTAINS : bis-[4-(2,3-epoxipropoxi)phenyl]propane), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) CONTAINS : bis-[4-(2,3-epoxipropoxi)phenyl]propane), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) CONTAINS : bis-[4-(2,3-epoxipropoxi)phenyl]propane), 9, III
14.3. Transport hazard class(es)			
9	9	9	9
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: True	Dangerous for the environment: True Marine pollutant: Yes	Dangerous for the environment: True	Dangerous for the environment: True
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13
Hazard identification number (Kemler No.)	: 90
Orange plates	:



DRY FLEX® 1 2-in-1 - Component A

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

Tunnel restriction code (ADR) : -
EAC code : •3Z

Transport by sea

Special provisions (IMDG) : 274, 335, 969
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : LP01, P001
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-F
Stowage category (IMDG) : A
MFAG-No : 171

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L
Special provisions (IATA) : A97, A158, A197, A215
ERG code (IATA) : 9L

Inland waterway transport

Classification code (ADN) : M6
Special provisions (ADN) : 274, 335, 375, 601
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Carriage permitted (ADN) : T
Equipment required (ADN) : PP
Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : M6
Special provisions (RID) : 274, 335, 375, 601
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, IBC03, LP01, R001
Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions (RID) : TP1, TP29
Tank codes for RID tanks (RID) : LGBV
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12
Special provisions for carriage - Loading, unloading and handling (RID) : CW13, CW31
Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 90

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

DRY FLEX® 1 2-in-1 - Component A

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

UK REACH Annex XVII (Restriction List)

UK restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	DRY FLEX® 1 2-IN-1 - Component A ; oxirane, mono[(C12-14-alkyloxy)methyl] derivs. ; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol ; bis-[4-(2,3-epoxipropoxy)phenyl]propane	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	DRY FLEX® 1 2-IN-1 - Component A ; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol ; bis-[4-(2,3-epoxipropoxy)phenyl]propane	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

UK REACH Annex XIV (Authorisation List)

This product contains no substance(s) listed on UK REACH Annex XIV (Authorisation List) equal to or above the 0.1% level of disclosure

UK REACH Candidate List (SVHC)

Contains no substance(s) listed on the UK REACH Candidate List

GB PIC regulation (Prior Informed Consent)

This product contains no substance(s) listed on the GB PIC List equal to or above the level of SDS disclosure

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (S.I. No. 168 of 2015)

This product contains no substance(s) listed on the GB Ozone Depletion List equal to or above the level of SDS disclosure

Control of Poisons and Explosives Precursors Act

This product contains no substance(s) listed as a reportable poison on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This product contains no substance(s) listed as a regulated poison on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This product contains no substance(s) listed as a reportable explosive precursor on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This substance is not listed as a regulated poison on the Control of Poisons and Explosives Precursors Regulations

Drug Precursors Regulation (273/2004)

This product contains no substance(s) listed on the GB Drug Precursors List equal to or above the level of SDS disclosure

15.1.2. Other Information

VOC content : Without VOC (volatile organic compounds)

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Abbreviations and acronyms:

SDS	Safety Data Sheet
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
PBT	Persistent Bioaccumulative Toxic

DRY FLEX® 1 2-in-1 - Component A

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

Abbreviations and acronyms:

vPvB	Very Persistent and Very Bioaccumulative
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
LC50	Median lethal concentration
LD50	Median lethal dose
CAS	CAS (Chemical Abstracts Service) number
EG-nr	EINECS- en ELINCS-number
EINECS	European Inventory of Existing Commercial Substances
OEL	Occupational Exposure Limit

Data sources

: ECHA (European Chemicals Agency).

Other information

: REACH Disclaimer:

This information is based on current knowledge. Consistency of data in the SDS with CSR is considered, as far as the information is available at the time of compilation (cfr Revision date and Version number). **DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
EUH205	Contains epoxy constituents. May produce an allergic reaction.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 2	H411	Calculation method

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : DRY FLEX® 1 2-IN-1 - Component B

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use
Use of the substance/mixture : Elastic repair compound
Product only to be used in combination with component A.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Repair Care International B.V.
Cartografenweg 34
NL- 5141 MT Waalwijk
Nederland
T + 31(0) 416 650095
info@repair-care.com - www.repair-care.com

1.4. Emergency telephone number

Country/Area	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA Belfast	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to GB CLP (SI 2019:720 as amended)

Acute toxicity (oral), Category 4 H302
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 1 H318
Skin sensitisation, Category 1 H317
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation H335
Hazardous to the aquatic environment – Acute Hazard, Category 1 H400
Hazardous to the aquatic environment – Chronic Hazard, Category 1 H410

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Harmful if swallowed. Causes severe skin burns and eye damage. May cause respiratory irritation. May cause an allergic skin reaction. Very toxic to aquatic life with long lasting effects. Causes serious eye damage.

2.2. Label elements

Labelling according to GB CLP (SI 2019:720 as amended)

Hazard pictograms (GB CLP) :



GHS05

GHS07

GHS09

Signal word (GB CLP) : Danger

Contains : 2-ethyl-2-[(3-mercapto-1-oxopropoxy)methyl]propane-1,3-diyl bis[3-mercaptopropionate]; Mercapto compound; Bis[(dimethylamino)methyl]phenol

Hazard statements (GB CLP) : H302 - Harmful if swallowed.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.
H335 - May cause respiratory irritation.
H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements (GB CLP) : P261 - Avoid breathing vapours, mist.
P280 - Wear protective gloves, protective clothing, eye protection.
P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

DRY FLEX® 1 2-in-1 - Component B

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P391 - Collect spillage.
P501 - Dispose of contents and container to an approved waste disposal plant.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to GB CLP (SI 2019:720 as amended)
2-ethyl-2-[(3-mercapto-1-oxopropoxy)methyl]propane-1,3-diyl bis[3-mercaptopropionate]	CAS-No.: 33007-83-9 EC-No.: 251-336-1	< 60	Acute Tox. 4 (Oral), H302 (ATE=1000 mg/kg bodyweight) Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Mercapto compound	CAS-No.: Trade Secret	< 50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
2,4,6-tris(dimethylaminomethyl)phenol	CAS-No.: 90-72-2 EC-No.: 202-013-9 UK Index-No.: 603-069-00-0	< 25	Acute Tox. 4 (Oral), H302 (ATE=971 mg/kg bodyweight) Skin Irrit. 2, H315 Eye Irrit. 2, H319
Bis[(dimethylamino)methyl]phenol	CAS-No.: 71074-89-0 EC-No.: 275-162-0	< 5	Acute Tox. 4 (Oral), H302 (ATE=1673 mg/kg bodyweight) Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335
3-mercaptopropionic acid	CAS-No.: 107-96-0 EC-No.: 203-537-0	< 1	Met. Corr. 1, H290 Acute Tox. 3 (Oral), H301 (ATE=63 mg/kg bodyweight) Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=1,8 mg/l/4h) Skin Corr. 1B, H314 Eye Dam. 1, H318
Alcohols, C11-14-iso-, C13-rich	CAS-No.: 68526-86-3 EC-No.: 271-235-6	< 1	Skin Irrit. 2, H315 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
ethyl acetate stof met grenswaarde(n) voor blootstelling op de werkplek	CAS-No.: 141-78-6 EC-No.: 205-500-4 UK Index-No.: 607-022-00-5	0,0015 – 0,01	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Gently wash with plenty of soap and water. Get immediate medical advice/attention. Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Get immediate medical advice/attention. Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause respiratory irritation.

DRY FLEX® 1 2-in-1 - Component B

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking. Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Harmful if swallowed. Burns.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon oxides (CO, CO ₂).

5.3. Advice for firefighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Absorb spillage to prevent material damage.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. For further information refer to section 8: "Exposure controls/personal protection".
Concerning disposal/elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling	: Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Avoid extremely high (> 50 °C) or low (<5 °C) temperatures. Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Incompatible products	: Acids.
Storage temperature	: 20 °C ± 10°C
Heat and ignition sources	: Keep away from heat and direct sunlight.
Packaging materials	: Store always product in container of same material as original container.

7.3. Specific end use(s)

No additional information available

DRY FLEX® 1 2-in-1 - Component B

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

ethyl acetate (141-78-6)

United Kingdom - Occupational Exposure Limits

Local name	Ethyl acetate
WEL TWA (OEL TWA)	734 mg/m ³
	200 ppm
WEL STEL (OEL STEL)	1468 mg/m ³
	400 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Provide local exhaust or general room ventilation to minimize vapour concentrations. Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Protective clothing. Gloves. Protective goggles.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Protective goggles. DIN EN 166. Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Long sleeved protective clothing. ISO 13688

Hand protection:

Wear suitable gloves resistant to chemical penetration. Chemical resistant gloves (according to European standard NF ISO 374-1 or equivalent).
Wear suitable gloves resistant to chemical penetration

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves, Reusable gloves	Nitrile rubber (NBR), Polyvinylchloride (PVC)	6 (> 480 minutes)	≥0,11		EN ISO 374

DRY FLEX® 1 2-in-1 - Component B

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

8.2.2.3. Respiratory protection

Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation. In case of inadequate ventilation wear respiratory protection. EN 143

Respiratory protection			
Device	Filter type	Condition	Standard
Breathing apparatus	Type A - High-boiling (>65 °C) organic compounds	Vapour protection, Protection for Liquid particles	EN 143

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Paste.
Colour	: white.
Odour	: characteristic.
Odour threshold	: Not available
pH	: Not available
Melting point	: < 0 °C
Freezing point	: Not available
Boiling point	: > 100 °C
Flash point	: > 100 °C
Explosive limits	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Relative vapour density at 20°C	: > 1 (Air = 1)
Relative density	: 1,28 (Water = 1)
Density	: Not available
Solubility	: In water, material is partially soluble.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
Viscosity, kinematic	: Not available
Explosive properties	: Not available

9.2. Other information

VOC content	: Without VOC (volatile organic compounds)
Particle characteristics	: Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid extremely high (> 50 °C) or low (<5 °C) temperatures.

10.5. Incompatible materials

Acids.

10.6. Hazardous decomposition products

No decomposition if stored normally.

DRY FLEX® 1 2-in-1 - Component B

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

DRY FLEX® 1 2-IN-1 - Component B

ATE UK (oral)	1449,378 mg/kg bodyweight
---------------	---------------------------

2-ethyl-2-[(3-mercapto-1-oxopropoxy)methyl]propane-1,3-diyl bis[3-mercaptopropionate] (33007-83-9)

LD50 oral rat	1000 – 2000 mg/kg
---------------	-------------------

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)

LD50 oral rat	971 mg/kg
---------------	-----------

Bis[(dimethylamino)methyl]phenol (71074-89-0)

LD50 oral rat	1673 mg/kg
---------------	------------

3-mercaptopropionic acid (107-96-0)

LD50 oral rat	63 – 126 mg/kg
---------------	----------------

LC50 Inhalation - Rat (Dust/Mist)	1,8 mg/l/4h
-----------------------------------	-------------

Alcohols, C11-14-iso-, C13-rich (68526-86-3)

LD50 oral rat	> 2000 mg/kg
---------------	--------------

LD50 dermal rat	> 2000 mg/kg
-----------------	--------------

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause respiratory irritation.

Mercapto compound (Trade Secret)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

Bis[(dimethylamino)methyl]phenol (71074-89-0)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

ethyl acetate (141-78-6)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Very toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Very toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Very toxic to aquatic life with long lasting effects.

2-ethyl-2-[(3-mercapto-1-oxopropoxy)methyl]propane-1,3-diyl bis[3-mercaptopropionate] (33007-83-9)

LC50 - Fish [1]	0,156 mg/l (OECD 203; Oncorhynchus mykiss)
-----------------	--

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)

LC50 - Fish [1]	> 100 mg/l (OECD 203; Cyprinus carpio)
-----------------	--

DRY FLEX® 1 2-in-1 - Component B

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
EC50 - Crustacea [1]	> 100 mg/l (OECD 202; Daphnia magna)
ErC50 algae	46,7 mg/l (OECD 201; Pseudokirchneriella subcapitata)
NOEC chronic algae	≈ 1,13 mg/l (OECD 201; Pseudokirchneriella subcapitata)
3-mercaptopropionic acid (107-96-0)	
LC50 - Fish [1]	98 mg/l (OECD 203; Danio rerio)
EC50 - Crustacea [1]	9 mg/l (OECD 202; Daphnia magna)
ErC50 algae	26 mg/l (OECD 201; Pseudokirchneriella subcapitata)
NOEC chronic algae	4,1 mg/l (OECD 201; Pseudokirchneriella subcapitata)
Alcohols, C11-14-iso-, C13-rich (68526-86-3)	
LC50 - Fish [1]	0,42 mg/l (OECD 203; Oncorhynchus mykiss)
ErC50 algae	3,2 mg/l (OECD 201; Pseudokirchneriella subcapitata)
ethyl acetate (141-78-6)	
LC50 - Fish [1]	230 mg/l (Pimephales promelas)
NOEC chronic crustacea	2,4 mg/l (OECD 211; Daphnia magna)
NOEC chronic algae	> 100 mg/l (OECD 201; Desmodesmus subspicatus)
12.2. Persistence and degradability	
DRY FLEX® 1 2-IN-1 - Component B	
Persistence and degradability	Biodegradability in water: no data available.
2-ethyl-2-[(3-mercaptopropionyl)methyl]propane-1,3-diyl bis[3-mercaptopropionate] (33007-83-9)	
Persistence and degradability	Not readily biodegradable.
Mercapto compound (Trade Secret)	
Persistence and degradability	Rapidly degradable
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Persistence and degradability	Not readily biodegradable.
Bis[(dimethylamino)methyl]phenol (71074-89-0)	
Persistence and degradability	Biodegradability in water: no data available.
3-mercaptopropionic acid (107-96-0)	
Persistence and degradability	Readily biodegradable.
Alcohols, C11-14-iso-, C13-rich (68526-86-3)	
Persistence and degradability	Readily biodegradable.
ethyl acetate (141-78-6)	
Persistence and degradability	Readily biodegradable.
12.3. Bioaccumulative potential	
2-ethyl-2-[(3-mercaptopropionyl)methyl]propane-1,3-diyl bis[3-mercaptopropionate] (33007-83-9)	
Partition coefficient n-octanol/water (Log Pow)	2,8 (20 °C; pH 3,8)
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Partition coefficient n-octanol/water (Log Pow)	0,219 (21,5 °C)
3-mercaptopropionic acid (107-96-0)	
Partition coefficient n-octanol/water (Log Pow)	-0,232 (22 °C; pH 7)
Alcohols, C11-14-iso-, C13-rich (68526-86-3)	
Partition coefficient n-octanol/water (Log Pow)	4,2 – 5 (25 °C; pH 7)

DRY FLEX® 1 2-in-1 - Component B

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

ethyl acetate (141-78-6)

Partition coefficient n-octanol/water (Log Pow) 0,68 (25 °C; pH 7)

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.
European List of Waste (LoW, EC 2000/532)	: 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances
HP Code	: HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP6 - "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure. HP8 - "Corrosive:" waste which on application can cause skin corrosion. HP13 - "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number			
UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shipping name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : 2-ethyl-2-[(3-mercapto-1-oxopropoxy)methyl]propane-1,3-diyl bis[3-mercaptopropionate])	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : 2-ethyl-2-[(3-mercapto-1-oxopropoxy)methyl]propane-1,3-diyl bis[3-mercaptopropionate])	Environmentally hazardous substance, liquid, n.o.s. (CONTAINS : 2-ethyl-2-[(3-mercapto-1-oxopropoxy)methyl]propane-1,3-diyl bis[3-mercaptopropionate])	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : 2-ethyl-2-[(3-mercapto-1-oxopropoxy)methyl]propane-1,3-diyl bis[3-mercaptopropionate])
Transport document description			
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : 2-ethyl-2-[(3-mercapto-1-oxopropoxy)methyl]propane-1,3-diyl bis[3-mercaptopropionate]), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : 2-ethyl-2-[(3-mercapto-1-oxopropoxy)methyl]propane-1,3-diyl bis[3-mercaptopropionate]), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (CONTAINS : 2-ethyl-2-[(3-mercapto-1-oxopropoxy)methyl]propane-1,3-diyl bis[3-mercaptopropionate]), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : 2-ethyl-2-[(3-mercapto-1-oxopropoxy)methyl]propane-1,3-diyl bis[3-mercaptopropionate]), 9, III
14.3. Transport hazard class(es)			
9	9	9	9
			
14.4. Packing group			
III	III	III	III

DRY FLEX® 1 2-in-1 - Component B

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

ADR	IMDG	IATA	RID
14.5. Environmental hazards			
Dangerous for the environment: True	Dangerous for the environment: True Marine pollutant: Yes	Dangerous for the environment: True	Dangerous for the environment: True
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13
Hazard identification number (Kemler No.)	: 90
Orange plates	: 

Tunnel restriction code (ADR)	: -
EAC code	: •3Z

Transport by sea

Special provisions (IMDG)	: 274, 335, 969
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-F
Stowage category (IMDG)	: A
MFAG-No	: 153

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provisions (IATA)	: A97, A158, A197, A215

DRY FLEX® 1 2-in-1 - Component B

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

ERG code (IATA) : 9L

Inland waterway transport

Classification code (ADN) : M6
Special provisions (ADN) : 274, 335, 375, 601
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Carriage permitted (ADN) : T
Equipment required (ADN) : PP
Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : M6
Special provisions (RID) : 274, 335, 375, 601
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, IBC03, LP01, R001
Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions (RID) : TP1, TP29
Tank codes for RID tanks (RID) : LGBV
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12
Special provisions for carriage - Loading, unloading and handling (RID) : CW13, CW31
Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 90

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

UK REACH Annex XVII (Restriction List)

UK restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	ethyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	DRY FLEX® 1 2-IN-1 - Component B ; 2,4,6-tris(dimethylaminomethyl)phenol ; Bis[(dimethylamino)methyl]phenol ; 3-mercaptopropionic acid ; Alcohols, C11-14-iso-, C13-rich ; ethyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	DRY FLEX® 1 2-IN-1 - Component B ; Alcohols, C11-14-iso-, C13-rich	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	ethyl acetate	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in the GB classification and labelling list or not.

DRY FLEX® 1 2-in-1 - Component B

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

UK REACH Annex XIV (Authorisation List)

This product contains no substance(s) listed on UK REACH Annex XIV (Authorisation List) equal to or above the 0.1% level of disclosure

UK REACH Candidate List (SVHC)

This product contains no substance(s) listed on the UK REACH Candidate List (SVHC) above the 0.1% level of disclosure

GB PIC regulation (Prior Informed Consent)

This product contains no substance(s) listed on the GB PIC List equal to or above the level of SDS disclosure

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (S.I. No. 168 of 2015)

This product contains no substance(s) listed on the GB Ozone Depletion List equal to or above the level of SDS disclosure

Control of Poisons and Explosives Precursors Act

This product contains no substance(s) listed as a reportable poison on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This product contains no substance(s) listed as a regulated poison on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This product contains no substance(s) listed as a reportable explosive precursor on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This substance is not listed as a regulated poison on the Control of Poisons and Explosives Precursors Regulations

Drug Precursors Regulation (273/2004)

This product contains no substance(s) listed on the GB Drug Precursors List equal to or above the level of SDS disclosure

15.1.2. Other Information

VOC content : Without VOC (volatile organic compounds)

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Indication of changes (UK)

Section	Changed item	Comments
	Supersedes	Added
	Revision date	Added
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Modified
2.2	Precautionary statements (GB CLP)	Modified
2.2	Signal word (GB CLP)	Modified
2.2	Hazard pictograms (GB CLP)	Modified
2.2	Hazard statements (GB CLP)	Modified
3	Composition/information on ingredients	Modified
11.1	ATE GB CLP (oral)	Modified

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level

DRY FLEX® 1 2-in-1 - Component B

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

Abbreviations and acronyms:	
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Data sources

: ECHA (European Chemicals Agency).

Other information

: REACH Disclaimer:

This information is based on current knowledge. Consistency of data in the SDS with CSR is considered, as far as the information is available at the time of compilation (cfr Revision date and Version number). **DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Full text of H- and EUH-statements:	
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1

DRY FLEX® 1 2-in-1 - Component B

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law.

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Met. Corr. 1	Corrosive to metals, Category 1
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Acute Tox. 4 (Oral)	H302	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H335	Calculation method
Aquatic Acute 1	H400	Calculation method
Aquatic Chronic 1	H410	Calculation method